



DOSATRON®

WATER POWERED DOSING TECHNOLOGY

14 GPM: D14MZ2


Product Specifications

Dilution Range:	1:500 to 1:50 (0.2% to 2%)
Water Flow Range:	0.05 to 14 GPM
Operating Pressure Range:	4.3 to 85 PSI
Available Housing Materials:	<ul style="list-style-type: none">• Polypropylene (Standard Blue)• PVDF (White)
Dimensions:	19 1/18" x 6 5/16"
Weight:	6 lbs
Connection Size:	3/4" NPT
Maximum Temperature:	104° F
Included Accessories:	6' clear suction tube, strainer, weight, mounting bracket and operating manual
Recommended Accessories:	IPK34



Basic Installation

IPK34 - 14 GPM Industrial Plumbing Kit



IPK34 - 14 GPM

- A - 3/4" schedule 80 PVC ball valve
- B - 3/4" brass pressure regulator w/gauge
- C - 3/4" poly 200 mesh tee filter
- D - 3/4" brass 14 GPM flow restrictor
- E - 3/4" schedule 80 PVC union ball check
- F - (4) 3/4" x 2" schedule 80 PVC nipples
- G - 3/4" union

For units:
D14MZ2
D14MZ5
D14MZ10

Dosatron International
2090 Sunnydale Blvd. • Clearwater, FL, USA
800-523-8499 • www.dosatronusa.com